Tel.: (215)723-6051

Safety Data Sheet acc. to OSHA HCS

Printing date 05/28/2020 Reviewed on 05/28/2020

1 Identification

- · Product identifier
- · Trade name: Dynapoxy Healer Sealer Part A
- · Article number: 142989A
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Pecora Corporation

165 Wambold Road

Harleysville, PA 19438

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident

involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapor.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

H304 May be fatal if swallowed and enters airways. Asp. Tox. 1

- · Label elements
- GHS label dements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS05

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Solvent naphtha (petroleum), light arom.

4-nonylphenol, branched

2,3-epoxypropyl o-tolyl ether

· Hazard statements

Flammable liquid and vapor.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

(Contd. on page 2)

Printing date 05/28/2020 Reviewed on 05/28/2020

Trade name: Dynapoxy Healer Sealer - Part A

(Contd. of page 1)

Suspected of damaging fertility or the unborn child.

May be fatal if swallowed and enters airways.

Precautionary statements

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 3 Fire = 2 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)	≥25-<60%	
	1,2,4-trimethylbenzene	≥10-<12%	
64742-95-6	Solvent naphtha (petroleum), light arom.	≥0.1-<11%	
2210-79-9	2,3-epoxypropyl o-tolyl ether	≥ 2.5-<7.5%	
84852-15-3	4-nonylphenol, branched	≥5-<5.5%	
108-67-8	mesitylene	≥2.5-<3.25%	
25340-17-4	diethylbenzene	≤1.4%	
98-82-8	cumene	≥0.25-<0.6%	
100-41-4	ethylbenzene	≥0.1-<0.2%	

 \cdot **Additional information:** For the wording of the listed hazard phrases refer to section 16.

US

Printing date 05/28/2020 Reviewed on 05/28/2020

Trade name: Dynapoxy Healer Sealer - Part A

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms recieve medical treatment.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Seek medical treatment.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, sand, extinguishing powder. Do not use water.

Foam

- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 05/28/2020 Reviewed on 05/28/2020

Trade name: Dynapoxy Healer Sealer - Part A

See Section 13 for disposal information.

(Contd. of page 3)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage: cool and dry
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

95-63-6	95-63-6 1,2,4-trimethylbenzene			
REL	Long-term value: 125 mg/m³, 25 ppm			
TLV	Long-term value: 123 mg/m³, 25 ppm			
108 - 67	-8 mesitylene			
REL	Long-term value: 125 mg/m³, 25 ppm			
TLV	Long-term value: 123 mg/m³, 25 ppm			
25340-	25340-17-4 diethylbenzene			
WEEL	Long-term value: 5 ppm			
98-82-8	98-82-8 cumene			
PEL	Long-term value: 245 mg/m³, 50 ppm Skin			
REL	Long-term value: 245 mg/m³, 50 ppm Skin			
TLV	Long-term value: (246) NIC-0.5 mg/m³, (50) NIC-0.1 ppm NIC-A3			

(Contd. on page 5)

Printing date 05/28/2020 Reviewed on 05/28/2020

Trade name: Dynapoxy Healer Sealer - Part A

(Contd. of page 4)

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 87 mg/m³, 20 ppm

· Ingredients with biological limit values:

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection: Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: According to product specification

Odor: Characteristic
Odor threshold: Not determined.

(Contd. on page 6)

Printing date 05/28/2020 Reviewed on 05/28/2020

Trade name: Dynapoxy Healer Sealer - Part A

	(Contd. of page
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	153 °C (307.4 °F)
· Flash point:	38 °C (100.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	450 °C (842 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures a
	possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	5 hPa (3.8 mm Hg)
· Density at 20 °C (68 °F):	1.109 g/cm³ (9.25461 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	25 %
Solids content:	75.0 %
· Other information	No further relevant information available.
· Volatile Organic Compounds:	Contains less than 250 g/L.

10 Stability and reactivity

- · Reactivity No decomposition if stored and applied as directed.
- · Chemical stability No decomposition if stored and applied as directed
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Keep away from heat and sources of ignition.
- · Incompatible materials: No further relevant information available.

(Contd. on page 7)

Printing date 05/28/2020 Reviewed on 05/28/2020

Trade name: Dynapoxy Healer Sealer - Part A

(Contd. of page 6)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

LD/LC50 values that are relevant for classification:			
95-63-6 1,2,4-trimethylbenzene			
Oral	LD50	5,000 mg/kg (rat)	
64742-95-6 Solvent naphtha (petroleum), light arom.			
Oral	LD50	>6,800 mg/kg (rat)	
Dermal	LD50	>3,400 mg/kg (rab)	
Inhalative	LC50/4 h	>10.2 mg/l (rat)	

- · Primary irritant effect:
- · on the skin: May cause skin irritation.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic.

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)			
1330-20-7	xylene	3	
98-82-8	aimene	2B	
100-41-4	ethylbenzene	2B	
71-43-2	benzene	1	
108-88-3	toluene	3	
· NTP (Nati	onal Toxicology Program)		
98-82-8 cı	imene	R	
71-43-2 be	enzene	K	
· OSHA-Ca	· OSHA-Ca (Occupational Safety & Health Administration)		
71-43-2 be	71-43-2 benzene		

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 8)

Printing date 05/28/2020 Reviewed on 05/28/2020

Trade name: Dynapoxy Healer Sealer - Part A

(Contd. of page 7)

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

· UN-Number	
· DOT	NA1993
· ADR. IMDG. IATA	UN1993

· UN proper shipping name

DOT COMBUSTIBLE LIQUID, N.O.S (Aromatic Solvent)

· ADR 1993 FLAMMABLE LIQUID, N.O.S. (Aromatic Solvent),

ENVIRONMENTALLY HAZARDOUS

• IMDG FLAMMABLE LIQUID, N.O.S. (Aromatic Solvent), MARINE

POLLUTANT

· IATA FLAMMABLE LIQUID, N.O.S. (Aromatic Solvent)

- · Transport hazard class(es)
- $\cdot DOT$







· Class 3 Combustible liquids

Label 3, 8

(Contd. on page 9)

Printing date 05/28/2020 Reviewed on 05/28/2020

Trade name: Dynapoxy Healer Sealer - Part A

	(Contd. of page 8)
· ADR	
· Class · Label	3 Flammable liquids 3+8
· IMDG	
· Class · Label	3 Flammable liquids 3/8
· IATA	
· Class · Label	3 Flammable liquids 3 (8)
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards: · Marine pollutant:	Product contains environmentally hazardous substances: 4- nonylphenol, branched, reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight = 700) Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category 	Warning: Flammable liquids 38 F-E, <u>S-E</u> A
· Transport in bulk according to Annex II of MAI and the IBC Code	RPOL73/78 Not applicable.
· Transport/Additional information:	
· DOT · Remarks:	Add "Marine Pollutant" to end of proper shipping name if shipping in a bulk container (>119 gallons). Special marking with the symbol (fish and tree). Not a Regulated Material shipping less than 119 gallons per container.
	(Contd. on page 10)

Printing date 05/28/2020 Reviewed on 05/28/2020

Trade name: Dynapoxy Healer Sealer - Part A

	(Contd. of page
· ADR	
· Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Remarks:	Not a Regulated Material shipping less than 119 gallons pecontainer.
· U.S. Domestic Ground Shipments:	Same as listed for Standard Shipments above.
· U.S. Domestic Ground Non-Bulk (119 gal or less per	•
container) Shipments:	DOT: Not regulated (Reclassified as per 49CFR 173.150).
Emergency Response Guide (ERG) Number:	Not determine
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (AROMATIO
o	SOLVENT), 3 (8), III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

95-63-6 1.2.4-trimethylbenzene

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

75-05-0	1,2,4-ir imethytoenzene	=10- <12/0
84852-15-3	4-nonylphenol, branched	≥5-<5.5%
1330-20-7	xylene	< 0.6%
98-82-8	cumene	≥0.25-<0.6%
100-41-4	ethylbenzene	≥0.1-<0.2%
71-43-2	benzene	< 0.1%
108-88-3	toluene	< 0.1%
· TSCA (Tox	ic Substances Control Act):	
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weig 700)	ht = ACTIVE
95-63-6	1,2,4-trimethylbenzene	<i>ACTIVE</i>
64742-95-6	Solvent naphtha (petroleum), light arom.	<i>ACTIVE</i>
2210-79-9	2,3-epoxypropyl o-tolyl ether	<i>ACTIVE</i>
84852-15-3	4-nonylphenol, branched	<i>ACTIVE</i>
108-67-8	mesitylene	<i>ACTIVE</i>
		(Contd. on page 11

≥10-<12%

Printing date 05/28/2020 Reviewed on 05/28/2020

Trade name: Dynapoxy Healer Sealer - Part A

		Contd. of pag
25340-17-4	diethylbenzene	ACT
1330-20-7	xylene	ACT
98-82-8	cumene	ACT.
100-41-4	ethylbenzene	ACT
71-43-2	benzene	ACT
108-88-3	toluene	ACT
Hazardous	Air Pollutants	
1330-20-7	xylene	
98-82-8	ситепе	
100-41-4	ethylbenzene	
71-43-2	benzene	
108-88-3	toluene	
Proposition	1 65	
Chemicals	known to the State of California (Prop. 65) to cause cancer:	
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 7	(00)
64742-95-6	Solvent naphtha (petroleum), light arom.	
98-82-8	cumene	
100-41-4	ethylbenzene	
71-43-2	benzene	
Chemicals	known to cause reproductive toxicity for females:	
	e ingredients is listed.	
Chemicals	known to cause reproductive toxicity for males:	
71-43-2 be		
Chemicals	known to cause developmental toxicity:	
71-43-2 b	· · · · · ·	
108-88-3 t		
	nity categories ronmental Protection Agency)	
,	1,2,4-trimethylbenzene	II
	mesitylene	II
1330-20-7	•	I
98-82-8	•	D, C
	ethylbenzene	D, C
71-43-2	•	A, K
108-88-3		II
		11
,	shold Limit Value established by ACGIH)	
1330-20-7	•	
	ethylbenzene	
71-43-2		
1/10/00/2	toluene	

Printing date 05/28/2020 Reviewed on 05/28/2020

Trade name: Dynapoxy Healer Sealer - Part A

(Contd. of page 11)

	(Cont.	. or page 11)	
· MAK (German Maximum Workplace Concentration)			
100-41-4	ethylbenzene	<i>3A</i>	
71-43-2	benzene	1	
· NIOSH-	Ca (National Institute for Occupational Safety and Health)		

71-43-2 benzene

- · **GHS label dements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms









GHS02

GHS05

GHS07

- · Signal word Danger
- Hazard-determining components of labeling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Solvent naphtha (petroleum), light arom.

4-nonylphenol, branched

2.3-epoxypropyl o-tolyl ether

· Hazard statements

Flammable liquid and vapor.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May be fatal if swallowed and enters airways.

· Precautionary statements

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- · Water hazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environmental, Health & Safety Department

(Contd. on page 13)

Printing date 05/28/2020 Reviewed on 05/28/2020

Trade name: Dynapoxy Healer Sealer - Part A

(Contd. of page 12)

- · Contact: Environmental, Health & Safety Manager
- · Date of preparation / last revision 05/28/2020 / 55
- · Abbreviations and acronyms:

ADR: Accord europé en sur le transport des marchandises dange reuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Muta. 1B: Germ cell mutagenicity - Category 1B

Carc. 1B: Carcinogenicity - Category 1B

Repr. 2: Reproductive toxicity – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

US